

Appl. No. 10/632,672
Response Dated September 29, 2005
Reply to Office Action mailed June 29, 2005

Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims

1. (currently amended) A damper comprising:
at least one damper vane;
a motor coupled to the damper vane to move the damper vane;
a first port operable in an input mode or an output mode;
a second port operable in an input mode when the first port is operable in the output mode, and operable in an output mode when the first port is operable in the input mode; and
a microcontroller coupled to the first and second ports, wherein the first port operates in the input mode upon receipt of a signal at the first port, and the second port operates in the output mode.
2. (original) The damper of claim 1, further comprising a microcontroller coupled to the first and second ports.
3. (canceled)
4. (currently amended) The damper of claim ~~[[3]]~~ 1, wherein the second port operates in the input mode upon receipt of a signal at the second port, and the first port operates in the output mode.
5. (original) The damper of claim 1, wherein the first and second ports both define jack cavities configured to receive identically-shaped plugs.

Appl. No. 10/632,672
Response Dated September 29, 2005
Reply to Office Action mailed June 29, 2005

6. (original) A damper comprising:
 - at least one damper vane;
 - a motor coupled to the damper vane to move the damper vane;
 - a first port including an input stage configured to receive an input and an output stage configured to send an output;
 - a second port including an input stage configured to receive an input and an output stage configured to send an output; and
 - a microcontroller coupled to the first and second ports, wherein the microcontroller monitors the first and second ports and designates the second port as an output upon receipt of a control signal from the input stage of the first port.
7. (previously presented) The damper of claim 6, wherein the microcontroller sends the control signal on the output stage of the second port.
8. (previously presented) The damper of claim 7, wherein the microcontroller is configured to undesignate the second port after sending the control signal on the output stage of the second port.
9. (previously presented) The damper of claim 6, wherein the first and second ports both define jack cavities configured to receive plugs.
10. (original) The damper of claim 9, wherein the jack cavities of the first and second ports are identical in shape.
11. (original) The damper of claim 6, wherein the first and second ports are interchangeable.

Appl. No. 10/632,672
Response Dated September 29, 2005
Reply to Office Action mailed June 29, 2005

12. (original) An air handling system comprising:
a source of conditioned air; and
an air-handling assembly coupled to the source of conditioned air, the air-handling assembly including:

a diffuser;

a damper including at least one damper vane and a motor coupled to the damper vane to move the damper vane, as well as a first port including an input stage configured to receive an input and an output stage configured to send an output, and a second port including an input stage configured to receive an input and an output stage configured to send an output; and

a microcontroller coupled to the first and second ports, wherein the microcontroller monitors the first and second ports and designates the second port as an output upon receipt of a control signal from the input stage of the first port, and wherein the microcontroller sends the control signal on the output stage of the second port.

13. (original) The system of claim 12, wherein the first and second ports are identical in shape and interchangeable.

14. (original) The system of claim 12, further comprising another air-handling assembly coupled to the source of conditioned air, the air-handling assembly including:

a diffuser;

a damper including at least one damper vane and a motor coupled to the damper vane to move the damper vane, as well as a first port including an input stage configured to receive an input and an output stage configured to send an output, and a second port including an input stage configured to receive an input

Appl. No. 10/632,672
Response Dated September 29, 2005
Reply to Office Action mailed June 29, 2005

and an output stage configured to send an output; and

a microcontroller coupled to the first and second ports, wherein the microcontroller monitors the first and second ports and designates the second port as an output upon receipt of a control signal from the input stage of the first port, and wherein the microcontroller sends the control signal on the output stage of the second port.

15-16. (canceled)